


TECHNICAL PARAMETERS

Name		Data
Basic	Operating weight	2650 kg
	Standard bucket Capacity	0.08 m³
	Standard bucket Width	580 mm
	Max.Travel speed	2.6/4.4km/h
	Max.Swing speed	10 rpm
	Grade ability	30°
	Ground pressure	25.1 kPa
	Max.Traction force	30.7 KN
	Boom swing angle (L/R)	65°/50°
	Engine brand	YANMAR
Engine	Engine model	3TNV80F
	Rated power	14.6 kW/2400 rpm
	Displacement	1.267 L
	Fuel tank	26 L
	Max.Flow(total)	2×28.8+19.2+6.5 L/min
Hydraulic	Max.Working pressure	23.5 MPa
	Max.Pilot pressure	3.2 Mpa
	Max.Arm digging force	14(15.8) kN
	Max.Bucket digging force	24 kN
	Hrdraulic oil tank	41 L
Chassis	Track width	300 mm
	Track type	Steel crawler
	Carrier rollers number	1(each side)
	Track rollers number	4(each side)
Electric	System vollage	12 V
	Battery capacity	12 V,45 Ah





PRODUCT FEATURES

Yanmar strong power engine, which meet U.S. EPA Tier 4 Final, EU Stage V. The combination of zero-tail swing and boom deviation is designed for narrow and complicated working scenarions.

Wider space and view are provide by enlarged front windscreen and sunroof.

Color monitoring digital and analogue combined display

The door and hood can be opened completely to ensure easy and convenient maintenance.

STANDARD EQUIPMENT

OPTIONAL EQUIPMENT

Fops/Tops cabin		
Suspension seat		
Warm air blower		
Hydraulic pilot control rod		
Deflectable boom		
Warning light		
Breaker pipeline		

lectro-hydraulic proportional joystick Front safeguard ops/Tops canopy 300mm width bucket 1000mm width bucket Quick hitch pipeline 300mm rubber tracks



Efficiency Rules the Future



The following blank can be used for notes or comments

For more information on Lonking products, Please contact our local agent;

Lonking, Lonking CDM Series and their respective logos, as well as corporate identity in this leaflet are trademarks of Lonking Holdings Ltd. and may not be used without written permission. 2024/05

Specifications and design are subject to change without prior notice. Machines shown may not include optional accessories

LONKING (FU JIAN) INTERNATIONAL TRADE CO., LTD.

Add: 26 Minyi Road, Xinqiao, Songjiang Industrial Zone, Shanghai E-mail: export@lonking.cn http://www.lonkinggroup.com Tel: +86-21-3760 2242

CDM6025 MINI EXCAVATOR

OPERATING WEIGHT:	2650kg
ENGINE POWER:	14.6kW
BUCKET CAPACITY:	0.08m³
TRAVEL SPEED:	2.6/4.4km/h